

SESSION 2022



29" front and rear (stock configuration)

Mino Low

	Seat tube length	Stem length	Reach	Stack	Effective top tube	Chainstay length	Head tube angle	Head tube length	Effective seat angle	Actual seat angle	BB drop	BB height	Standover	Wheelbase	Front center	Fork axle-to-crown	Fork offset	Trail	Rear travel	Front travel
R1	425	50	440	638.6	587.3	439	63.0	117	76.50	61	22.5	350	747	1255.2	811.1	600	56	126.9	200	200
R2	450	50	465	638.6	618.3	445	63.0	117	76.50	61	22.5	350	751	1286.2	842.1	600	56	126.9	200	200
R3	450	50	493	638.6	653.3	452	63.0	117	76.50	61	22.5	350	749	1321.2	877.1	600	56	126.9	200	200

Mino High

R1	425	50	446.8	633.9	585.8	435.1	63.6	117	77.1	61.6	13.9	358.6	754.6	1251.9	811.1	600	56	122.3	204.2	200
R2	450	50	471.6	633.7	616.8	441.1	63.6	117	77.1	61.6	13.7	358.8	758.7	1282.9	842.1	600	56	122.4	204.2	200
R3	450	50	499.4	633.5	651.8	448.2	63.6	117	77.1	61.6	13.6	358.9	756.8	1317.9	877.1	600	56	122.5	204.2	200

29" front, 27.5" rear - Mino High (required)

Mino High

	Seat tube length	Stem length	Reach	Stack	Effective top tube	Chainstay length	Head tube angle	Head tube length	Effective seat angle	Actual seat angle	BB drop	BB height	Standover	Wheelbase	Front center	Fork axle-to-crown	Fork offset	Trail	Rear travel	Front travel
R1	425	50	438.7	639.5	587.6	435.1	62.9	117	76.4	60.9	13.5	349.2	746.4	1252.3	817.5	601	56	127.8	204.2	200
R2	450	50	463.7	639.5	618.6	441.1	62.9	117	76.4	60.9	13.4	349.2	750.4	1283.3	842.5	601	56	127.8	204.2	200
R3	450	50	491.8	639.6	653.6	448.2	62.9	117	76.4	60.9	13.4	349.2	748.4	1318.3	870.5	601	56	127.8	204.2	200

27.5 front and rear - Mino High (required + extended headset cup)

Mino High

R1	425	50	442.0	637.2	586.9	435.1	63.2	117	76.7	61.2	10.5	347.0	743.6	1245.4	810.5	582	46	129.2	204.2	200
R2	450	50	466.9	637.2	617.9	441.1	63.2	117	76.7	61.2	10.5	347.0	747.7	1276.4	835.5	582	46	129.2	204.2	200
R3	450	50	494.9	637.1	652.9	448.2	63.2	117	76.7	61.2	10.5	347.0	745.7	1311.4	863.5	582	46	129.3	204.2	200